



Technical Data

Document Reference

25/00000

R1718

RAMCRO - BMS-HFFR-BC-UnScreened Cable

For standard applications, flame retardant.

Multicore, PO-Insulation, UnScreened, LSZH/FRNC-Sheath

SSS0603HXEDX-RB

Application

LSZH - FRNC sheathed multi-conductor cables are suitable for Building Management Systems (BMS), Sound, Audio, Security, Safety, Control and Instrumentation.

Construction

		Unit	Nominal Value
Formation	6 Cores		
Section	16 AWG		
Conductor	Plain annealed copper wire, Multistrand	mm	1.5
Insulation	Polyolefine	mm	1.9
Colour Code	Black, Red, White, Green, Brown, Blue		
Individual Screen	N.A.		
Wrapping	at least 1 layer of plastic tape 0,023 mm		
Collective Screen	N.A.		
Inner Sheath	N.A.		
Armour	N.A.		
Outer Sheath	Thermoplastic Low Smoke, Halogen Free - LSZH (FRNC) - Purple RAL 4005	mm	6.8
Cable Printing	RAMCRO ITALY R1718 AUDIO CONTROL & INSTRUMENTATION CABLE 6C 16AWG UNSCREENED LSZH (FRNC) 300 V 75 C IEC 60332-1/UL 1581 - SSS0603HXEDX-RB- "PROD.WEEK/20" + BATCH + METER MARKING		

Technical Data & Standard References

Fire Propagation:		Type of Cable:	BMS-HFFR-BC-UnScreened Cable
- Test on single cable	IEC 60332-1	Low Voltage Directive	2014/35/UE
- Test on bunched cables	IEC 60332-3	Other References:	
Limiting Oxygen Index (LOI)	(min 37%)		
Smoke Density	IEC 61034		
Amount of halogen acid gas	IEC 60754-1 (max 0,5%)		
Acidity (ph value) and conductivity	IEC 60754-2		
Sunlight resistance	UL 1581 section 1200		
Notes			

Electrical & Mechanical Data

Conductor Cross-section	Nom.	16 AWG	Temperature Range:	
DC Resistance per core at 20° C	max Ω /km	15.47	During Operation	° C -30°C up to 80°C
Insulation Resistance at 20° C	min $M\Omega$ *km	25	During Installation	° C -30°C up to 80°C
Nominal Mutual Capacitance	max pF/m	74		
Inductance	max mH/km	1	Min. Bending Radius	mm 8 x cable diameter
Test Voltage - Core/Core	V	2000	Max Pulling Tension	N 347
Test Voltage - Core/Screen	V	N.A.	Weight Approx	kg/km 103
Operating Voltage	V	300	Put up length	mt 305



Issued by: RAMCRO S.p.A.

Prepared by RAMCRO Tech

Via Marzorati, 15 - 20014 Nerviano - Milan - Italy / www.ramcro.it

Date of issue:

9/22/2026 0:00