Technical Data

Document Reference
25/00000

R1740

RAMCRO - BMS-HFFR-BC-UnScreened Cable
For standard applications, flame retardant.

Multicore, PO-Insulation, UnScreened, LSZH/FRNC-Sheath

SSS0806HXEDX-RB

Application
LSZH - FRNC sheathed multi-conductor cables are suitable for Building Management Systems (BMS), Sound, Audio, Security, Safety, Control and Instrumentation.

Construction

		Unit	Nominal Value
Formation	8 Cores		
Section	20 AWG		
Conductor	Plain annealed copper wire, 7 strand	mm	0.9
Insulation	Polyolefine	mm	1.3
Colour Code	Black, Red, White, Green, Brown, Blue, Orange, Yellow		
Individual Screen	N.A.		
Wrapping	at least 1 layer of plastic tape 0,023 mm		
Collective Screen	N.A.		
Inner Sheath	N.A.		
Armour	N.A.		
Outer Sheath	Thermoplastic Low Smoke, Halogen Free - LSZH (FRNC) - Purple RAL 4005	mm	5.6
Cable Printing	RAMCRO ITALY R1740 AUDIO CONTROL & INSTRUMENTATION CABLE 8C 20AWG UNSCREENED LSZH (FRNC) 300 V 75 C IEC 60332-1/UL 1581 - SSS0806HXEDX-RB - "PROD.WEEK/20" + BATCH + METER MARKING		

Technical Data & Standard References

Fire Propagation:	
- Test on single cable	IEC 60332-1
- Test on bunched cables	IEC 60332-3
Limiting Oxygen Index (LOI)	(min 37%)
Smoke Density	IEC 61034
Amount of halogen acid gas	IEC 60754-1 (max 0,5%)
Acidity (ph value) and conductivity	IEC 60754-2
Sunlight resistance	UL 1581 section 1200
Notes	

Type of Cable:	BMS-HFFR-BC-UnScreened Cable
Low Voltage Directive	2014/35/UE
Other References:	

Electrical & Mechanical Data

Conductor Cross-section	Nom.	20 AWG
DC Resistance per core at 20° C	max Ω/km	37.5
Insulation Resistance at 20° C	min MΩ*km	25
Nominal Mutual Capacitance	max pF/m	70
Inductance	max mH/km	1
Test Voltage - Core/Core	V	2000
Test Voltage - Core/Screen	V	N.A.
Operating Voltage	V	300

Temperature Range:		
During Operation	° C	-30°C up to 80°C
During Installation	° C	-30°C up to 80°C
Min. Bending Radius	mm	8 x cable diameter
Max Pulling Tension	N	187
Weight Approx	kg/km	66
Put up length	mt	305