

RAMCRO - DATA LAN RS-485 Cable For standard applications, flame retardant.

Multipair, PE-Insulation, Double Screened, PVC-Sheath

MAR0208HBADX-T-RB

Application

Balanced digital circuit. Medium speed fieldbus interfaces. Maximum transmission speed 35 Mbit/second (normal use 1 or 0.5 Mbit/sec). Max. transmission distance is 1200 metres, 32 nodes per bus. Cables used have mainly 24AWG conductors, one twisted pair or multi-pair and impedance of 120 Ohm.

Construction

Formation	2 Pairs	Unit	Nominal Value
Section	24 AWG		
Conductor	Tinned copper wire, 7 strand	mm	0,6
Insulation	Polyetilene - PE	mm	1,8
Colour Code	White/Blue, Blue/White, White/Orange, Orange/White		
Individual Screen	N.A.		
Wrapping	at least 1 layer of plastic tape 0,023 mm		
Collective Screen	Aluminium / PETP + Tinned Copper Braid		
Inner Sheath	N.A.		
Armour	N.A.		
Outer Sheath	Polyvinyl chloride - PVC - Grey RAL 7001	mm	8,4
Cable Printing	RAMCRO ITALY R1190 DATA LAN CABLE - RS 485 - 2PR 24AWG SCREENED 300 V 75 C IEC 60332-1/UL 1581 - MAR0208HBADX-T-RB "PROD.WEEK/18" + BATCH + METER MARKING		

Technical Data & Standard References

Fire Propagation:		Type of Cable:	DATA LAN RS-485 Cable
- Test on single cable	IEC 60332-1	Low Voltage Directive	2014/35/UE
- Test on bunched cables	IEC 60332-3	Other References:	
Limiting Oxygen Index (LOI)	(min 30%)		
Smoke Density	IEC 61034		
Amount of halogen acid gas	IEC 60754-1 (max 15%)		
Acidity (ph value) and conductivity	IEC 60754-2		
Sunlight resistance	UL 1581 section 1200		
Notes			

Electrical & Mechanical Data

Conductor Cross-section	Nom.	24 AWG	Temperature Range:		
DC Resistance per core at 20° C	max	Ω/km	91	During Operation	° C -30°C up to 80°C
Insulation Resistance at 20° C	min	MΩ*km	5000	During Installation	° C -30°C up to 80°C
Nominal Mutual Capacitance	max	pF/m	41		
Inductance	max	mH/km	1	Min. Bending Radius	mm 8 x cable diameter
Test Voltage - Core/Core	V	2000		Max Pulling Tension	N/mm2 41
Test Voltage - Core/Screen	V	2000		Weight Approx	kg/km 66
Operating Voltage	V	300		Put up length	mt 305

Issued by: RAMCRO S.p.A.



Date of issue:

Prepared by RAMCRO Tech

Via Marzorati, 15 - 20014 Nerviano - Milan - Italy / www.ramcro.it

24/01/2019 00:00

Creator: LDG

Transfer to third parties only under authorization by Ramcro S.p.A.

Empty Form

Printing errors excepted. Subject to alterations.