

Applications

Building Management Systems (BMS), Access Control, Instrumentation

Sector - BT BMS-TEC®

Computer Cables

Standard References

IEC 60332-1
RoHS directives
(BS)EN 50290

Note: © BT BMS-Tec is a registered trade mark of British Telecommunications public limited company.

Design

1. Conductor

N x 2 x Tinned Copper wire, 24AWG flexible (7x32)

2. Insulation

Polyvinyl Chloride (PVC)

Pair 1: Black & Red

Pair 2: Black & White

Pair 3: Black & Green

Pair 4: Black & Blue

Pair 5: Black & Yellow

Pair 6: Black & Brown

Pair 7: Black & Orange

Pair 8: Red & White

3. Drain Wire

24 AWG (7 x 32)
Tinned Copper

4. Screen

Aluminium/Polyester
100% Coverage

5. Sheath Material

Polyvinyl Chloride (PVC)

Standard Put Up Length

305 metres

Physical Characteristics

BTCL Part Number	Unit	C1181	C1182	C1183	C1184	C1185	C1186	C1187	C1188
No of pairs		1	2	3	4	5	6	7	8
Nom. Diameter Conductor	mm	0.6	0.6	0.6	0.6	0.6	0.6	0.6	0.6
Nom. Radial Thickness Insulation	mm	0.25	0.25	0.25	0.25	0.25	0.25	0.25	0.25
Nom. Radial Thickness Sheath	mm	0.8	0.8	0.8	0.6	0.6	0.4	0.4	0.4
Nom. Overall Diameter	mm	4.0	5.6	5.9	6.7	7.3	7.4	7.5	8.3

Electrical Characteristics

BTCL Part Number	Unit	C1181	C1182	C1183	C1184	C1185	C1186	C1187	C1188
No of pairs		1	2	3	4	5	6	7	8
Max. DC Resistance Conductor	Ω/km	88	88	88	88	88	88	88	88
Max. DC Resistance Screen	Ω/km	78.4	78.4	78.4	78.4	78.4	78.4	78.4	78.4
Nominal Impedance	Ω	75	75	75	75	75	75	75	75
Capacitance core to core	pF/m	135	76	76	80	80	80	80	80
Capacitance core to other cores.+screen	pF/m	275	122	122	130	130	130	130	130
Nominal Inductance	µH/m	0.62	0.62	0.62	0.62	0.62	0.62	0.62	0.5
Nominal Velocity of Propagation	%	60	60	60	60	60	60	60	60
Max. Recommen. Current @ 25°C	Amps	1.76	1.76	1.76	1.5	1.5	1.1	1.1	1.1
Max. Operating Voltage	Vrms	300	300	300	300	300	300	300	300

Miscellaneous

BTCL Part Number	Unit	C1181	C1182	C1183	C1184	C1185	C1186	C1187	C1188
No of pairs		1	2	3	4	5	6	7	8
Max. Recommend. Pulling Tension	N	45	90	135	180	225	270	315	360
Min. Bend Radius (install)	mm	40	56	59	67	73	74	75	83
Nominal Cable Weight	kg/km	18	28	39	48	57	65	73	85
Operating Temperature	°C	-25 / +75							